



180-L ducted water heater

TDF 190/1,5

[✉ Send by e-mail](#) [🖨 Print](#)

Its benefits

- Automatic, weekly, anti-legionella function.
- Multiple safeguards: pressure valve, double safeguard against rises in temperature.
- No contamination risk: the condenser coil is outside the tank.
- Easy to install: closed refrigeration circuit - no intervention required.
- Anode and enamel provide anti-scale and anti-corrosion protection.

Product presentation

IDENTITY CARD



180-L ducted water heater
TDF 190/1,5

Range: Thermodynamic water heater

[Download product leaflet in PDF](#)

Characteristics products

Unités intérieures	HWHM-TDF190/15-H31
Unités extérieures 1 ~230V - 50Hz	-
Unités extérieures 3 ~400V - 50Hz - N	-

COOLING

Rated capacity	kw	
SEER / Energy label		/
Operating limits	°C	

HEATING

Rated capacity	kW	3900/17
SCOP (average climate) / Energy label (average climate)		/
Operating limits	°C	

INDOOR UNIT

Sound pressure level to 1 m (LS/MS/HS/SS)	dB(A)	
Outline Dimensions (WxHxD)	mm	ø 560 mm - 1760 H
Net Weight	kg	107
Code		7HPO30004
Energy label		-

OUTDOOR UNIT

Sound pressure level to 1 m (LS/MS/HS/SS)	dB(A)	
Outline Dimensions (WxHxD)	mm	
Net Weight	kg	
Code 1-230V - 50 Hz		-
Code 3-400V - 50 Hz		-
Energy label		See the label

Accessories and options

ADAPTATION KIT, 90° BEND AND 1M DUCT (TDF 190)

EXTENTION KIT 1M DUCT (TDF 190)

Réf. : 7ACEL1735
Appareils : TDF 190

Adaptation kit, 90° bend and 1m duct

Réf. : 7ACEL1736
Appareils : TDF 190

Extention kit 1m duct