



280-L ducted water heater

TDF 300/3,5

[Send by e-mail](#) [Print](#)

Its benefits

- Automatic, weekly, anti-legionella function.
- Multiple safeguards: pressure valve, double safeguard against rises in temperature (manual/automatic).
- No contamination risk: the condenser coil is outside the tank.
- Easy to install: closed refrigeration circuit - no intervention required.
- Anode and enamel or stainless provide anti-scale and anti-corrosion protection

Product presentation

IDENTITY CARD



280-L ducted water heater

TDF 300/3,5

Range: Thermodynamic water heater

Characteristics products

Unités intérieures	AWHM-TDF300/3.5-H31	AWHM-TDF300/3.5-H31
Unités extérieures 1 ~230V - 50Hz	-	-
Unités extérieures 3 ~400V - 50Hz - N	-	-

COOLING

Rated capacity	kw		
SEER / Energy label		/	/
Operating limits	°C		

HEATING

Rated capacity	kW	4300/18.7	4300/18.7
SCOP (average climate) / Energy label (average climate)		/	/
Operating limits	°C		

INDOOR UNIT

Sound pressure level to 1 m (LS/MS/HS/SS)	dB(A)		
Outline Dimensions (WxHxD)	mm	ø 650 mm - 1920 H	ø 650 mm - 1920 H
Net Weight	kg	145.5	145.5
Code		7HPO30005	7HPO30007
Energy label		-	-

OUTDOOR UNIT

Sound pressure level to 1 m (LS/MS/HS/SS)	dB(A)		
Outline Dimensions (WxHxD)	mm		
Net Weight	kg		
Code 1-230V - 50 Hz		-	-
Code 3-400V - 50 Hz		-	-
Energy label		See the label	See the label

Accessories and options

ADAPTATION KIT, 90° BEND AND 1M DUCT (TDF 300)

EXTENTION KIT 1M DUCT (TDF 300)

Réf. : 7ACEL1737
Appareils : TDF 300

Adaptation kit, 90° bend and 1m duct

Réf. : 7ACEL1738
Appareils : TDF 300

Extention kit 1m duct