



Cassette CAF

[Send by e-mail](#) [Print](#)


Cassette fixed speed not compatible in Europe

Its benefits

- Wireless remote control provided as standard and wired remote control provided as option.
- Operating in low condition down to -15°C in cooling.
- Centralized controller up to 16 units including weekly timer (optional).

Product presentation

IDENTITY CARD



Cassette
CAF

Range: Cassette

This product is only available outside
Europe

[Download product leaflet in PDF](#)

COMFORT FUNCTION



Multiflow 360°

USER FUNCTIONS



I Feel



Programmable
timer

INSTALLER FUNCTIONS



Error code via
indoor unit



Self diagnostic

Characteristics products

Unités intérieures	AWSI-CAFo12- N11	AWSI-CAFo18- N11	AWSI-CAFo24- N11	AWSI-CAFo30- N11	AWSI-CAFo36- N11	AWSI-CAFo48- N11
Unités extérieures 1 ~230V - 50Hz	AWAU-YIFo12- H11	AWAU-YIFo18- H11	AWAU-YIFo24- H11	AWAU-YIFo30- H11	-	-
Unités extérieures 3 ~400V - 50Hz - N	-	-	-	-	AWAU-YIFo36- H13	AWAU-YIFo48- H13

COOLING

Rated capacity	kw	3.55	5	7	8.5	10	14.1
SEER / Energy label		/ D	/ E	/ C	/ B	/ C	/ C
Operating limits	°C	-15°/46° Dry Bulb	-15°/46° Dry Bulb	-15°/46° Dry Bulb	-15°/46° Dry Bulb	-15°/46° Dry Bulb	-15°/46° Dry Bulb

HEATING

Rated capacity	kW	3.7	5.4	7.6	9	11.5	15
SCOP (average climate) / Energy label (average climate)		/ D	/ D	/ C	/ B	/ B	/ D
Operating limits	°C	-7°/24° Dry Bulb	-10°/24° Dry Bulb	-10°/24° Dry Bulb	-10°/24° Dry Bulb	-10°/24° Dry Bulb	-10°/24° Dry Bulb

INDOOR UNIT

Sound pressure level to 1 m (LS/MS/HS/SS)	dB(A)	38/40/42	46/47/49	46/47/48	48/49/50	43/46/47	43/46/47
Outline Dimensions (WxHxD)	mm	665x240x595	665x240x595	840x240x840	840x240x840	840x320x840	840x320x840
Net Weight	kg	19.5	20	27	27	32	33
Code		7SP042257	7SP042252	7SP042253	7SP042254	7SP042255	7SP042256
Energy label		-	-	-	-	-	-

OUTDOOR UNIT

Sound pressure level to 1 m (LS/MS/HS/SS)	dB(A)	52	56	54	59	60	60
Outline Dimensions (WxHxD)	mm	848x540x320	955x700x395	955x700x395	980x790x425	980x790x425	1120x1100x440
Net Weight	kg	33.5	53	61	69	69	103
Code 1-230V - 50 Hz		7SP062907	7SP062901	7SP062902	7SP062903	-	-
Code 3-400V - 50 Hz		-	-	-	-	7SP062904	7SP062905
Energy label		-	-	-	-	-	-