



Cassette monosplit CCD

[Send by e-mail](#) [Print](#)

360° flow with round corners

Its benefits

- 360° flow.
- Twin application.
- Fresh air intake (for models 24 to 48).
- Water pump included.
- G1 filter.

Product presentation

IDENTITY CARD



Cassette monosplit
CCD

Range: Cassette

[Download product leaflet in PDF](#)

HEATING



DC Inverter

AIR QUALITY



Air filter



Fresh air

COMFORT FUNCTION



Multiflow 360°

INSTALLER FUNCTIONS



Error code via indoor unit



Self diagnostic



Alarm output



Dry contact on/off

USER FUNCTIONS



I Feel



Programmable timer

Characteristics products

Unités intérieures	AWSI- CCD009X-N11	AWSI- CCD012-N11	AWSI- CCD018-N11	AWSI- CCD024-N11	AWSI- CCD036-N11	AWSI- CCD036-N11	AWSI- CCD048-N11
Unités extérieures 1 ~230V - 50Hz	-	AWAU- YMD012-H11	AWAU- YMD018-H11	AWAU- YMD024-H11	AWAU- YMD036-H11	-	-
Unités extérieures 3 ~400V - 50Hz - N	-	-	-	-	-	AWAU- YMD036-H13	AWAU- YMD048-H13

COOLING

Rated capacity	kw	2.6 (0.8-3.3)	3.5 (0.8-4.1)	5.1 (0.8-6.1)	6.8 (1.2-8.2)	10.5 (2.9-12.0)	10.5 (2.9-12.0)	14.0 (4.0-16.1)
SEER / Energy label	/	/	6.8 / A++	6.3 / A++	6.1 / A++	6.1 / A++	6.1 / A++	5.6 / A+
Operating limits	°C	-15°/50° Dry bulb	-15°/50° Dry bulb	-15°/50° Dry bulb	-15°/50° Dry bulb	-15°/50° Dry bulb	-15°/50° Dry bulb	-15°/50° Dry bulb

HEATING

Rated capacity	kW	2.9 (0.85-3.7)	4.1 (0.5-4.4)	5.6 (0.9-7.0)	7.6 (1.2-8.6)	11.2 (2.6-13.2)	11.2 (2.6-13.2)	15.5 (4.2-17.6)
SCOP (average climate) / Energy label (average climate)	/	/	4.0 / A+	4.0 / A+	4.0 / A+	4.0 / A+	4.0 / A+	4.0 / A+
Operating limits	°C	-15°/24° Dry bulb	-15°/24° Dry bulb	-15°/24° Dry bulb	-15°/24° Dry bulb	-15°/24° Dry bulb	-15°/24° Dry bulb	-15°/24° Dry bulb

INDOOR UNIT

Sound pressure level to 1 m (LS/MS/HS/SS)	dB(A)	32/36/39	35/39/43	36/40/44	42/44/47	48/51/54	48/51/54	46/49/52
Outline Dimensions (WxHxD)	mm	570x270x570	570x260x570	570x270x570	840x245x840	840x245x840	840x245x840	840x287x840
Net Weight	kg	14.5	16.2	16.5	24	26.4	26.4	28
Code		7SPO42246X	7SPO42247	7SPO42248	7SPO42249	7SPO42250	7SPO42250	7SPO42251
Energy label		-	See the label	See the label	See the label	See the label	See the label	See the label

OUTDOOR UNIT

Sound pressure level to 1 m (LS/MS/HS/SS)	dB(A)		56	54	60	61	61	63
Outline Dimensions (WxHxD)	mm		800x554x333	800x554x333	845x702x363	946x810x410	946x810x410	952x415x1333
Net Weight	kg		29.9	35.5	49	67.2	81	108.1
Code 1-230V - 50 Hz		-	7SPO62970	7SPO62892	7SPO62893	7SPO62895	-	-
Code 3-400V - 50 Hz		-	-	-	-	-	7SPO62896	7SPO62899
Energy label		See the label	See the label	See the label	See the label	See the label	See the label	See the label

Accessories and options

WIRELESS CONTROLLER RC08C



Réf. : 7ACEL1740

Appareils : HRD/DID

Timer, eco mode, "Follow me" option, swing, technician mode.

WIRED SINGLE CONTROL RCW6



Réf. : 7ACEL1704

Appareils : DID/CCD/FCD

Mode, fan speed, real time, timer, temperature, weekly timer, swing and "I

Feel".

WIRED SINGLE CONTROL RCW8



Réf. : 7ACEL1706

Appareils : HKD/CCD/XBD/FCD

Mode, fan speed, timer ON/OFF, temperature and swing.

CENTRAL CONTROLLER RCW16



Réf. : 7ACEL1707

Appareils : HRD/DID/CCD/FCD/FWDB

Controls up to 64 indoor units with individual setting failure codes indication, ON-OFF dry contact, last operation memory, Modbus.

BMS GATEWAY



Réf. : 7ACEL1708

Appareils : DID/CCD/FCD/FWDB

Maximum 1024 units could be connected (16 gateways).