



Ducted DAF



[Send by e-mail](#) [Print](#)

Ducted fixed speed not compatible in Europe

Its benefits

- Wired remote control provided as standard.
- Operating in low condition down to -15°C in cooling.
- Centralized controller up to 16 units including weekly timer (optional).

Product presentation

IDENTITY CARD



Ducted
DAF

Range: Ducted

This product is only available outside

Europe

[Download product leaflet in PDF](#)

USER FUNCTIONS



I Feel



Programmable
timer

INSTALLER FUNCTIONS



Error code via
indoor unit



Self diagnostic

Characteristics products

Unités intérieures	AWSI- DAF012-N11	AWSI- DAF018-N11	AWSI- DAF024-N11	AWSI- DAF030-N11	AWSI- DAF036-N11	AWSI- DAF048-N11	AWSI- DAF060-N11
Unités extérieures 1 ~230V - 50Hz	AWAU- YIF012-H11	AWAU- YIF018-H11	AWAU- YIF024-H11	AWAU- YIF030-H11	-	-	-
Unités extérieures 3 ~400V - 50Hz - N	-	-	-	-	AWAU- YIF036-H13	AWAU- YIF048-H13	AWAU- YIF060-H13

COOLING

Rated capacity	kw	3.60	5.00	7.00	8.30	10.00	14.00	16.00
SEER / Energy label		/ D	/ E	/ C	/ C	/ D	/ C	/ C
Operating limits	°C	-15°/46° Dry Bulb	-15°/46° Dry Bulb	-15°/46° Dry Bulb	-15°/46° Dry Bulb	-15°/46° Dry Bulb	-15°/46° Dry Bulb	-15°/46° Dry Bulb

HEATING

Rated capacity	kW	3.70	5.40	7.40	8.80	11.50	15.00	18.00
SCOP (average climate) / Energy label (average climate)		/ D	/ D	/ C	/ C	/ B	/ D	/ C
Operating limits	°C	-7°/24° Dry Bulb	-10°/24° Dry Bulb	-10°/24° Dry Bulb	-10°/24° Dry Bulb	-10°/24° Dry Bulb	-10°/24° Dry Bulb	-10°/24° Dry Bulb

INDOOR UNIT

Sound pressure level to 1 m (LS/MS/HS/SS)	dB(A)	34/36/37	29/30/33	32/34/38	44/45/46	44/46/48	50/-/52	49/-/52
Outline Dimensions (WxHxD)	mm	700x200x485	1015x275x720	1260x270x555	1260x270x555	1230x290x790	1230x290x790	1235x330x830
Net Weight	kg	18.5	31	33	34	46	53	56
Code		7SP032177	7SP032171	7SP032172	7SP032173	7SP032174	7SP032175	7SP032176
Energy label		-	-	-	-	-	-	-

OUTDOOR UNIT

Sound pressure level to 1 m (LS/MS/HS/SS)	dB(A)	52	56	54	59	60	60	61
Outline Dimensions (WxHxD)	mm	848x540x320	955x700x395	955x700x395	980x790x425	980x790x425	1120x1100x440	980x1350x410
Net Weight	kg	33.5	53	61	69	69/74	103/115	118/129
Code 1-230V - 50 Hz		7SP062907	7SP062901	7SP062902	7SP062903	-	-	-
Code 3-400V - 50 Hz		-	-	-	-	7SP062904	7SP062905	7SP062906
Energy label		-	-	-	-	-	-	-