

Ducted low static pressure DAV


[Send by e-mail](#) [Print](#)

Its benefits

- 220 ultra thin design and space saving.
- Optional air return design.
- High efficiency filter.
- EEV inside.
- Wired controller RWV05 included on standard.
- Ideal for hotel.

Product presentation

IDENTITY CARD



Ducted low static pressure

DAV

Range: VRF

Characteristics products

Unités intérieures	AWSI-DAV007-N11	AWSI-DAV009-N11	AWSI-DAV012-N11	AWSI-DAV016-N11
Unités extérieures 1 ~230V - 50Hz	-	-	-	-
Unités extérieures 3 ~400V - 50Hz - N	-	-	-	-

COOLING

Rated capacity	kw	2.2	2.8	3.6	4.5
SEER / Energy label		/	/	/	/
Operating limits	°C				

HEATING

Rated capacity	kW	2.5	3.2	4	5
SCOP (average climate) / Energy label (average climate)		/	/	/	/
Operating limits	°C				

INDOOR UNIT

Sound pressure level to 1 m (LS/MS/HS/SS)	dB(A)				
Outline Dimensions (WxHxD)	mm	610x220x500	610x220x500	610x220x500	1105x220x500
Net Weight	kg	15	15	16	25
Code		7SP03H001	7SP03H002	7SP03H003	7SP03H004
Energy label		-	-	-	-

OUTDOOR UNIT

Sound pressure level to 1 m (LS/MS/HS/SS)	dB(A)				
Outline Dimensions (WxHxD)	mm				
Net Weight	kg				
Code 1-230V - 50 Hz		-	-	-	-
Code 3-400V - 50 Hz		-	-	-	-
Energy label		See the label	See the label	See the label	See the label

Accessories and options

RWV05



Réf. : 7ACELH021

Appareils : High wall, cassette, ducted, floor ceiling

Unit operating, group control (max. 16 indoor units) and "I Feel" function.

WATER PUMP

Réf. : 7ACTL0529

Appareils : DAV

REC01



Réf. : 7ACELHO09

Appareils : Ducted

Realize infrared control for duct type

RWV07



Réf. : 7ACELHO24

Appareils : High wall, cassette, ducted, floor ceiling

Single unit control, group control, max. 16 units, weekly timer, clock, mode cooling/heating/auto/airflow/dehumidification, temperature, fan speed, fan direction

RWV03



Réf. : 7ACELHO08

Appareils : All (except for console type)

Unit operating and group control (max. 16 indoor units)