



Ducted medium static pressure monosplit DLSE+VAV

✉ Send by e-mail 🖨 Print

Its benefits

- Solution Volume d'Air Variable.
- Programmation hebdomadaire.
- Pompe à condensats intégrée.
- Super silencieux.

Product presentation

IDENTITY CARD



Ducted medium static pressure
monosplit
DLSE+VAV

Range: Ducted

HEATING



DC Inverter

COMFORT FUNCTION



Sleep mode



Super quiet

USER FUNCTIONS



I Feel



24 H
Programmable
timer

INSTALLER FUNCTIONS



Self diagnostic

FUNCTION



Turbo mode



Low battery
indication



Auto restart
(memory)



Remote
control lock

OUTDOOR UNIT CAPACITY



Low ambient
cooling -10°C



Low ambient
heating -15°C

Characteristics products

Unités intérieures	AWSI-DLSE018-N11	AWSI-DLSE024-N11	AWSI-DLSE030-N11	AWSI-DLSE036-N11	AWSI-DLSE036-N11	AWSI-DLSE043-N11	AWSI-DLSE043-N11
Unités extérieures 1 ~230V - 50Hz	AWAU-YBDE018-H11	AWAU-YBDE024-H11	AWAU-YBDE030-H11	AWAU-YBD036-H11	-	AWAU-YBD042-H11	-
Unités extérieures 3 ~400V - 50Hz - N	-	-	-	-	AWAU-YBD036-H13	-	AWAU-YAD042-H13

COOLING

Rated capacity	kw	5	6.8	7.5	9.5	9.5	12.5	12.5
SEER / Energy label		5.8 / A+	5.4 / A	5.5 / A	5.6 / A+	4.7 / B	3.35 / A	3.51 / A
Operating limits	°C	-10°/46° Dry bulb	-10°/46° Dry bulb	-10°/46° Dry bulb	-10°/46° Dry bulb	-10°/46° Dry bulb	-10°/46° Dry bulb	-10°/46° Dry bulb

HEATING

Rated capacity	kW	5.6	7.6	8.6	10.5	11.6	14	14
SCOP (average climate) / Energy label (average climate)		3.9 / A	3.8 / A	3.9 / A	3.8 / A	3.9 / A	3.41 / B	3.51 / B
Operating limits	°C	-15°/24° Dry bulb	-15°/24° Dry bulb	-15°/24° Dry bulb	-15°/24° Dry bulb	-15°/24° Dry bulb	-15°/24° Dry bulb	-15°/24° Dry bulb

INDOOR UNIT

Sound pressure level to 1 m (LS/MS/HS/SS)	dB(A)	35/38/41/43	38/42/45/48	39/43/46/48	41/45/46/48	41/45/46/48	42/46/53	42/46/53
Outline Dimensions (WxHxD)	mm	960x300x855	960x300x855	960x300x855	1005x345x915	1005x345x915	1005x345x915	1005x345x915
Net Weight	kg	29	30	31	33	33	33	33
Code		7SP032154	7SP032155	7SP032156	7SP032157	7SP032157	7SP032087	7SP032087
Energy label		-	-	-	-	-	-	-

OUTDOOR UNIT

Sound pressure level to 1 m (LS/MS/HS/SS)	dB(A)	53	55	56	58	58	58	58
Outline Dimensions (WxHxD)	mm	900x700x340	900x700x340	900x860x340	900x970x340	900x970x340	900x1250x340	900x1250x340
Net Weight	kg	56	61	66	80	85	110	110
Code 1-230V - 50 Hz		7SP061886	7SP061887	7SP061922	7SP061923	-	7SP061815	-
Code 3-400V - 50 Hz		-	-	-	-	7SP061900	-	7SP061757
Energy label		-	-	-	-	-	-	-

Accessories and options

WIRED GROUP CONTROL RCW2



Réf. : 7ACEL1212

Appareils : DLF/DLSE

• Controls up to 32 indoor units as a group or individually.

WIRELESS CONTROLLER RC08W



Réf. : 7ACEL1741

Appareils : DLF/DLSE

Operation mode, night mode, timer, I Feel, swing, clean mode...

- Option to set up to 15 group zones.
- Option to set timer (daily and weekly), mode, fan speed and swing.