



Floor ceiling SXT (TELECOM)



✉ Send by e-mail 🖨 Print

Solution fixed speed dédiée aux salles informatique

Its benefits

- Dedicated product for IT rooms.
- Treatment of corrosion on outdoor units and electronic cards.
- Wide operating temperature, dedicated product for communication rooms.

Product presentation

IDENTITY CARD



Floor ceiling
SXT (TELECOM)

Range: Floor ceiling
This product is only available outside
Europe

USER FUNCTIONS



I Feel

INSTALLER FUNCTIONS



Alarm output

Characteristics products

Unités intérieures	AWSI-SXT012-N11	AWSI-SXT018-N11	AWSI-SXT030-N11
Unités extérieures 1 ~230V - 50Hz	AWAU-YOFT012-H11	AWAU-YHF018-H11	-
Unités extérieures 3 ~400V - 50Hz - N	-	-	AWAU-YHF030-H13

COOLING

Rated capacity	kw	3.5	5.2	8.3
SEER / Energy label		2.9 / C	3.2 / E	3.4 / E
Operating limits	°C	-10°/50° Dry Bulb	-10°/50° Dry Bulb	-10°/50° Dry Bulb

HEATING

Rated capacity	kw			
SCOP (average climate) / Energy label (average climate)		/	/	/
Operating limits	°C			

INDOOR UNIT

Sound pressure level to 1 m (LS/MS/HS/SS)	dB(A)	41/46/52	41/46/52	45/49/54
Outline Dimensions (WxHxD)	mm	1068x675x235	1068x675x235	1285x675x235
Net Weight	kg	23	24	29
Code		7SP012245	7SP012226	7SP012229
Energy label		-	-	-

OUTDOOR UNIT

Sound pressure level to 1 m (LS/MS/HS/SS)	dB(A)	55	60	61
Outline Dimensions (WxHxD)	mm	780x540x250	900x700x340	900x860x340
Net Weight	kg	28/30	50/53	78/82
Code 1-230V - 50 Hz		7SP062918	7SP061924	-
Code 3-400V - 50 Hz		-	-	7SP061925
Energy label		-	-	-

Accessories and options

WIRED SINGLE CONTROL RCW8



Réf. : 7ACEL1706

Appareils : HKD/CCD/XBD/FCD

Mode, fan speed, timer ON/OFF, temperature and swing.