



## Floor standing SDM

[Send by e-mail](#) [Print](#)

High volume room - DC Inverter technology

Its benefits

- DC Inverter technology.
- Commercial application.

## Product presentation

### IDENTITY CARD



Floor standing  
SDM

Range: Floor standing

[Download product leaflet in PDF](#)

### HEATING



DC Inverter

### AIR QUALITY



Air filter



Auto clean/dry

### INSTALLER FUNCTIONS



Error code via  
indoor unit



Self diagnostic

## Characteristics products

Unités intérieures	AW-SDM048-N11
Unités extérieures 1 ~230V - 50Hz	AW-YSDM048-H11
Unités extérieures 3 ~400V - 50Hz - N	-

## COOLING

Rated capacity	kw	12.5 (6.0-14.5)
SEER / Energy label		5.1 / A
Operating limits	°C	-10°/46° Dry bulb

## HEATING

Rated capacity	kW	13.0 (6.0-16.5)
SCOP (average climate) / Energy label (average climate)		3.4 / A
Operating limits	°C	-15°/24° Dry bulb

## INDOOR UNIT

Sound pressure level to 1 m (LS/MS/HS/SS)	dB(A)	44/48/51
Outline Dimensions (WxHxD)	mm	1850x600x350
Net Weight	kg	57
Code		7SPO11088
Energy label		-

## OUTDOOR UNIT

Sound pressure level to 1 m (LS/MS/HS/SS)	dB(A)	59
Outline Dimensions (WxHxD)	mm	1008x830x410
Net Weight	kg	82
Code 1-230V - 50 Hz		7SPO62971
Code 3-400V - 50 Hz		-
Energy label		-