



High wall HBV

[✉ Send by e-mail](#) [🖨 Print](#)

Its benefits

- Quiet.
- 3D and long distance air supply.
- Hidden screen.
- Two sides drain.

Product presentation

IDENTITY CARD



High wall
HBV

Range: VRF

Characteristics products

Unités intérieures	AWSI-HBV007-N11	AWSI-HBV009-N11	AWSI-HBV012-N11	AWSI-HBV018-N11	AWSI-HBV024-N11
Unités extérieures 1 ~230V - 50Hz	-	-	-	-	-
Unités extérieures 3 ~400V - 50Hz - N	-	-	-	-	-

COOLING

Rated capacity	kw	2.2	2.8	3.6	5.6	7.1
SEER / Energy label		/	/	/	/	/
Operating limits	°C					

HEATING

Rated capacity	kW	2.5	3.2	4	6.3	8
SCOP (average climate) / Energy label (average climate)		/	/	/	/	/
Operating limits	°C					

INDOOR UNIT

Sound pressure level to 1 m (LS/MS/HS/SS)	dB(A)					
Outline Dimensions (WxHxD)	mm					
Net Weight	kg					
Code		7SP02H012	7SP02H013	7SP02H014	7SP02H015	7SP02H016
Energy label		-	-	-	-	-

OUTDOOR UNIT

Sound pressure level to 1 m (LS/MS/HS/SS)	dB(A)					
Outline Dimensions (WxHxD)	mm					
Net Weight	kg					
Code 1-230V - 50 Hz		-	-	-	-	-
Code 3-400V - 50 Hz		-	-	-	-	-
Energy label		See the label	See the label	See the label	See the label	See the label

Accessories and options

RCV02



Réf. : 7ACELHO22

Appareils : All indoor units

Unit operating

RWV05



Réf. : 7ACELHO21

Appareils : High wall, cassette, ducted, floor ceiling

Unit operating, group control (max. 16 indoor units) and "I Feel" function.

RWV03

RWV07



Réf. : 7ACELHO08

Appareils : All (except for console type)

Unit operating and group control (max. 16 indoor units)



Réf. : 7ACELHO24

Appareils : High wall, cassette, ducted, floor ceiling

Single unit control, group control, max. 16 units, weekly timer, clock, mode cooling/heating/auto/airflow/dehumidification, temperature, fan speed, fan direction