



## Low temperature air/water monobloc heat pump

### PAC BT Monobloc

[✉ Send by e-mail](#) [🖨 Print](#)

Its benefits

- Cooling and heating mode.
- Monobloc system.
- Available in 3PH (sizes 14 to 16).
- High flexibility due to DC Inverter compressor.

## Product presentation

### IDENTITY CARD



Low temperature air/water  
monobloc heat pump  
PAC BT Monobloc

Range: Heat pump

[Download product leaflet in PDF](#)

### HEATING



DC Inverter

### COMFORT FUNCTION



Super quiet

## Characteristics products

Unités intérieures

Unités extérieures 1

~230V - 50Hz

Unités extérieures 3

~400V - 50Hz - N

COOLING

HEATING

INDOOR UNIT

Code

Energy label

OUTDOOR UNIT

Code 1-230V - 50 Hz

Code 3-400V - 50 Hz

Energy label

## Accessories and options

### 300 L DOMESTIC HOT WATER TANK KIT



Réf. : 7ACFH0662

Appareils : PAC BT MB

Optimised with the operation of the heat pump:

- Programmable anti-legionella function.
- Management of the three-way valve / circulator pump couple.
- 3.1 m<sup>2</sup> exchange surface.

### KIT FOR ELECTRICAL DHW TANK - TOP OUTLET



Réf. : 7ACFH0789

Plate exchanger and circulator pump kit for domestic hot water, top outlet (sensor supplied for installation in a thimble)

### KIT FOR ELECTRICAL DHW TANK - BOTTOM OUTLET



Réf. : 7ACFH0801

Plate exchanger and circulator pump kit for domestic hot water, bottom outlet (sensor supplied and installed)

### SETTLING FILTER (POT)

### ON-LINE ELECTRIC HEATER - 2/4/6 KW





Réf. : 7ACFH0666

Appareils : All Heat Pumps

Protect the heat pump from sludging and preserve optimum thermal exchange.

Réf. : 7ACFH0665

Installation inside the building, offers two power stages (2 and 4 kW, or 6 kW in total). Provides extra heating when the heating demand is greater than the capacity of the heat pump.

**FLOOR SUPPORT RUBBER RECYCLED (PAIR) LENGTH: 1 000 MM**



Réf. : 7ACTL0510

Appareils : All Heat Pumps

Necessary for a professional installation.