



## Window WFD

[Send by e-mail](#) [Print](#)

Prefabricated buildings solution - DC Inverter technology

Its benefits

- Unique solution.
- R32 refrigerant with low environmental impact.
- No fluid handling.

## Product presentation

### IDENTITY CARD



Window  
WFD

Range: Window

[Download product leaflet in PDF](#)

### HEATING



DC Inverter

### INSTALLER FUNCTIONS



Self diagnostic

## Characteristics products

Unités intérieures	AWWR-WFD009-C11	AWWR-WFD012-C11
Unités extérieures 1 ~230V - 50Hz	-	-
Unités extérieures 3 ~400V - 50Hz - N	-	-

## COOLING

Rated capacity	kw	2.75	3.7
SEER / Energy label		5.10 / A	5.10 / A
Operating limits	°C	18°/43° Dry bulb	18°/43° Dry bulb

## HEATING

Rated capacity	kW		
SCOP (average climate) / Energy label (average climate)		/	/
Operating limits	°C		

## INDOOR UNIT

Sound pressure level to 1 m (LS/MS/HS/SS)	dB(A)		
Outline Dimensions (WxHxD)	mm		
Net Weight	kg		
<b>Code</b>		<b>7WT010008</b>	<b>7WT010009</b>
Energy label		<a href="#">See the label</a>	<a href="#">See the label</a>

## OUTDOOR UNIT

Sound pressure level to 1 m (LS/MS/HS/SS)	dB(A)	45/47/49	45/47/49
Outline Dimensions (WxHxD)	mm	560x375x710	660x428x700
Net Weight	kg	34	46
<b>Code 1-230V - 50 Hz</b>		<b>-</b>	<b>-</b>
<b>Code 3-400V - 50 Hz</b>		<b>-</b>	<b>-</b>
Energy label		<a href="#">See the label</a>	<a href="#">See the label</a>